

# 7000 Online Controller

*Single and Dual Reader*



The 7000 is a 1 or 2-Door controller operated by computer control, available with Tcp/ip, Rs232, RS422, or Rs485. Tcp versions are available with POE, which can power readers and door strikes directly without the need for a power supply.

## Features & Options

- Online operation
- Wiegand, Prox, and Magstripe Support
- Barcode support
- DPS/RTE support
- Form C relay for each door
- Auxilliary RS232 device support
- Flash Upgradeable
- OEM versions available

## Interfaces

- TCP/IP (with POE)
- Rs232
- Rs485
- Rs422


  
International Bar Code

## Specifications

Reader Inputs:	2 Readers supporting prox,wiegand,magstripe, or barcode.
Sense Inputs:	2 inputs for each reader. Programmable for DPS and RTE functionality.
Relay:	6A 30vdc max, Form C
Power Requirement:	300ma @ 12vdc
Dimensions:	5" L x 5" W x 1" H
Enclosure:	Steel, 8.25"L x 8.25"W x 2"H
Weight	2 lb 15 oz
Operating Temperature	-40°C to +85°C
Standard Wiring:	RS232 (DB9), RJ45 (tcp/ip), Terminal Blocks (Rs422/485)

## How to Order

Ordering Codes.



### INTERFACE

TCP - C  
 TCP/POE - P  
 RS232 - S  
 RS422 /485- 2

### DOORS

1 - 1 Door  
 2 - 2 Doors

**Note - OEMS MAY BE ISSUED NON-STANDARD PART NUMBERS WHICH DO NOT CONFORM TO THE ABOVE STANDARD.**